

3-PHASE ONLINE UPS PI SERIES

(10KVA, 20KVA, 30KVA, 40KVA, 60KVA)



BENEFITS

- High frequency and double conversion on-line technology With fully digitized microprocessor control (DSP)
- Advanced PFC technology
- EPO function
- Wide input voltage range
- Parallel redundancy
- Lightning and surge protection, short circuit and overload protection
- Multilingual LCD and LED display

APPLICATION



Data center



Internet networks



Hospital & testing laboratories




Fire & alarm system




Servers

SCHEMATICS



10KVA - 40KVA



60KVA

FEATURES



WIDE INPUT RANGE



WALL-MOUNTABLE DESIGN



FARBER-TRANSFER™

Instant transfer of power through zero-crossing detection



FARBER-TECHTOR™

Protects against overload

SPECIFICATION

MODEL	FA-UPSX-192V-10KVA-3PH	FA-UPSX-240V-20KVA-3PH	FA-UPSX-192V-30KVA-3PH	FA-UPSX-240V-40KVA-3PH	FA-UPSX-480V-60KVA-3PH
Capacity(VA/Watts)	10KVA/8KW	20KVA/16KW	30KVA/24KW	40KVA/32KW	60KVA/48KW
INPUT					
Operating voltage range			274-478 V		
Operating frequency range			40-60Hz(50Hz)/50-70Hz(60Hz)		
Power factor			0.8		
OUTPUT					
Output voltage			380-400V		
Output frequency			50-60Hz		
Crest factor			3 to 1		
Efficiency			Line :≥90%, Batt:≥ 90%		
BATTERY					
DC voltage	192V DC		±192V DC	±240V DC	480V DC
Battery type	12V/9AH		12V/9AH		12V/65AH
Overload capability			loads 105-125%		
Transfer time			0 ms		
ENVIRONMENTAL					
operating temperature			0°C-40°C		
Storage temperature			0°C-45°C		
Humidity range			<95%		
Altitude			<1000m		
Noise level			≤60dB		
PHYSICAL					
Dimension D*W*H (mm)	560*260*720	720*260*720	720*260*720	720*260*721	910*515*1139



FARBER-TECHTOR™

Protects against short circuit



FARBER-TECHTOR™

Protects against over voltage



FARBER-TECHTOR™

Protects against under voltage



FARBER-WARNER™

In case of any fault or emergency,
an alarm will sound