

Model	FA-UPS-24V-9AH/2500VA
Capacity	2500 VA / 1500 W
INPUT	
Voltage	220/230/240 VAC
Voltage Range	162-290 VAC
Frequency Range	50/60 Hz (auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	±10%
Frequency Range (Batt. Mode)	50 Hz or 60 Hz ± 1 Hz
Waveform (Batt. Mode)	Modified sine wave
Transfer Time	2-6 ms typical
BATTERY	
Battery Type & Number	12V 9AH x 2
Typical Recharge Time	6-8 hours recover to 90% capacity, after full discharge
PROTECTION	
Full Protection	Overload, discharge, and overcharge protection
ALARM	
Battery Mode	Alarm every 10 seconds
Low Battery	Alarm every second
Overload	Alarm every 0.5 second
Fault	Continuous alarm
PHYSICAL	
Dimensions, D x W x H (mm)	436 x 145 x 213mm
ENVIRONMENT	
Humidity	0-90% RH @ 0- 40° C (non-condensing)
Noise Level	<40dB
MANAGEMENT	
USB & RS-232 Port	Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC