



FEATURES

- ✔ Design float life of 20years and cyclic life of 4000 cycles at 20% DOD
- ✔ Modular design for ease of installation and staching flexibility.
- ✔ Deep discharge capability .
- ✔ Patented lead Oxide Paste Recipe offering excellent charge acceptance and low self-discharge rate .
- ✔ Innovative Plate Design offers low internal resistance and superior high rate discharge performance .
- ✔ Advanced AGM separator offering a longer service life and enhanced high rate discharge performance.
- ✔ Unique Ribbed Desgin Polypropylene container and cover offering enhanced strength and durability for safe operation Superior high rate discharge with low internal resistance.

APPLICATION



SPECIFICATION

MODEL	VOLTAGE (V)	CAPACITY (AH)	WEIGHT (KG) ±5KG	DIMENSION IN MM (L x W x H)	FLOAT VOLTAGE PER CELL AT 27°C	BOOST VOLTAGE PER CELL AT 27°C
FA-BATT-24V-100AH-2V	24	100	97	350 x 706 x 236	2.23	2.3
FA-BATT-24V-120AH-2V	24	120	107	385 x 706 x 236	2.23	2.3
FA-BATT-24V-200AH-2V	24	200	166	350 x 706 x 355	2.23	2.3
FA-BATT-12V-240AH-2V	24	240	187	385 x 706 x 355	2.23	2.3
FA-BATT-12V-300AH-2V	12	300	125	500 x 706 x 200	2.23	2.3
FA-BATT-12V-375AH-2V	12	375	150	500 x 706 x 232	2.23	2.3
FA-BATT-12V-450AH-2V	12	450	175	500 x 706 x 262	2.23	2.3
FA-BATT-12V-600AH-2V	12	600	226	500 x 706 x 322	2.23	2.3

FEATURES

Recycle	MAINTENANCE	TEMPERATURE	WARRANTY	VENTILATION	CHARGING	DESIGN	LIFE
	Maintenance Free	Extreme Temperature caution	Warranty 1 year	Install the battery in a properly ventilated	After discharge, charge the battery immediately	Unique Design	100% cyclic life after 1200 cycles

2V BATTERIES

SPECIFICATION

MODEL	VOLTAGE (V)	CAPACITY (AH)	WEIGHT (KG) ±5KG	DIMENSION IN MM (L x W x H)	FLOAT VOLTAGE PER CELL AT 27°C	BOOST VOLTAGE PER CELL AT 27°C
FA-BATT-6V-750AH-2V	6	750	147	500 x 706 x 214	2.23	2.3
FA-BATT-6V-900AH-2V	6	900	173	500 x 706 x 214	2.23	2.3
FA-BATT-6V-1125AH-2V	6	1125	211	500 x 706 x 289	2.23	2.3
FA-BATT-6V-1350H-2V	6	1350	252	500 x 706 x 333	2.23	2.3
FA-BATT-12V-1800AH-2V	12	1800	978	500 x 706 x 966	2.23	2.3
FA-BATT-6V-2250AH-2V	6	2250	441	500 x 706 x 642	2.23	2.3
FA-BATT-6V-2700AH-2V	6	2700	519	500 x 706 x 732	2.23	2.3
FA-BATT-6V-3375AH-2V	6	3375	633	500 x 706 x 867	2.23	2.3
FA-BATT-6V-4050AH-2V	6	4050	756	500 x 706 x 999	2.23	2.3
FA-BATT-6V-4500AH-2V	6	4500	844	500 x 706 x 1156	2.23	2.3
FA-BATT-6V-5400AH-2V	6	5400	1008	500 x 706 x 1332	2.23	2.3
FA-BATT-12V-340AH-2V	12	340	138	555 x 706 x 200	2.23	2.3
FA-BATT-12V-425AH-2V	12	425	167	555 x 706 x 232	2.23	2.3
FA-BATT-12V-510AH-2V	12	510	195	555 x 706 x 262	2.23	2.3
FA-BATT-12V-680AH-2V	12	680	251	555 x 706 x 322	2.23	2.3
FA-BATT-6V-850AH-2V	6	850	164	555 x 706 x 214	2.23	2.3
FA-BATT-6V-1020AH-2V	6	1020	192	555 x 706 x 244	2.23	2.3
FA-BATT-6V-1530AH-2V	6	1275	235	555 x 706 x 289	2.23	2.3
FA-BATT-6V-1530AH-2V	6	1530	280	555 x 706 x 333	2.23	2.3
FA-BATT-12V-2040AH-2V	12	2040	753	555 x 706 x 966	2.23	2.3
FA-BATT-6V-2550AH-2V	6	2550	492	555 x 706 x 642	2.23	2.3
FA-BATT-6V-3060AH-2V	6	3060	576	555 x 706 x 732	2.23	2.3
FA-BATT-6V-3025AH-2V	6	3825	705	555 x 706 x 867	2.23	2.3
FA-BATT-6V-4590AH-2V	6	4590	840	555 x 706 x 999	2.23	2.3
FA-BATT-6V-5100AH-2V	6	5100	940	555 x 706 x 1156	2.23	2.3
FA-BATT-6V-6120AH-2V	6	6120	1120	555 x 706 x 1332	2.23	2.3
FA-BATT-12V-400AH-2V	12	400	155	500 x 706 x 232	2.23	2.3
FA-BATT-12V-200AH-2V	12	200	83	165 x 706 x 355	2.23	2.3