


# UPS DELTA SERIES

(850VA, 1200VA, 1500VA, 2500VA, 3000VA)



## APPLICATION



## BENEFITS

- ✓ This UPS is specially design for personal computers with multi-function
- ✓ The line of UPS is equipped with boost and buck AVR to stabilize input voltage range
- ✓ Microprocessor control guarantees high reliability.
- ✓ DC start function
- ✓ Auto restart with AC recovery
- ✓ Compact size, Light weight
- ✓ Provide AC Overload protection.

## FEATURES



WIDE INPUT RANGE



WALL-MOUNTABLE  
DESIGN



FARBER-TRANSFER™  
Instant transfer of  
power through zero-  
crossing detection



FARBER-TECHTOR™  
Protects against  
overload



Microprocessor  
Built-in controller  
ensures reliable,  
accurate and quick  
switching and  
performance



Buck-boost AVR  
Built-in automatic  
voltage regulator  
to overcome  
fluctuations in input  
source



## SPECIFICATION

MODEL NUMBER	FFA-UPSW-12V-850-1PH	FA-UPSW-24V-1200-1PH	FA-UPSW-24V-1500-1PH	FA-UPSW-36V-2500-1PH	FA-UPSW-48V-3000-1PH
Capacity	850 VA / 360 W	1200 VA / 600 W	1500 VA / 720 W	2500 VA / 1200 W	3000 VA / 1800W
<b>INPUT</b>					
Voltage	220/230/240 VAC				
Voltage Range	162-290 VAC				
Frequency Range	50/60 Hz (auto sensing)				
<b>OUTPUT</b>					
AC Voltage Regulation (Batt. Mode)	±10%				
Frequency Range (Batt. Mode)	50 Hz or 60 Hz ± 1 Hz				
Waveform (Batt. Mode)	Modified sine wave				
Transfer Time	2-6 ms typical				
<b>BATTERY</b>					
Battery Type & Number	12V 7AH x 1	12V 7AH x 2	12V 9AH x 2	12V 7AH x 3	12V 9AH x 4
Typical Recharge Time	6-8 hours recover to 90% capacity, after full discharge				
<b>PROTECTION</b>					
Full Protection	Overload, discharge, and overcharge protection				
<b>ALARM</b>					
Battery Mode	Alarm every 10 seconds				
Low Battery	Alarm every second				
Overload	Alarm every 0.5 second				
Fault	Continuous alarm				
<b>PHYSICAL</b>					
Dimensions, D x W x H (mm)	298 x 101 x 142mm	355 x 123 x 190mm	355 x 123 x 190mm	425 x 145 x 210mm	436 x 145 x 213mm
<b>ENVIRONMENT</b>					
Humidity	0-90% RH @ 0- 40°C (non-condensing)				
Noise Level	<40dB				
<b>MANAGEMENT</b>					
USB & RS-232 Port	Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC				



**FARBER-TECHTOR™**  
Protects against short circuit



**FARBER-TECHTOR™**  
Protects against over voltage



**FARBER-TECHTOR™**  
Protects against under voltage



**FARBER-WARNER™**  
In case of any fault or emergency, an alarm will sound



Fast transfer  
2-6 millisecond transfer time



Input  
162-290VAC input