

MODEL	FA-UPSX-36V-1KVA-1PH	FA-UPSX-36V-1.5KVA-1PH	FA-UPSX-48V-2KVA-1PH	FA-UPSX-72V-3KVA-1PH	FA-UPSX-240V-6KVA-1PH	FA-UPSX-240V-10KVA-1PH
PHASE	1 phase in/ 1 phase out					
Capacity(VA/Watts)	1000 VA/1000 W	1500 VA/1500 W	2000 VA/2000 W	3000 VA/3000 W	6000 VA/6000 W	10000 VA/10000 W
INPUT						
Input Voltage Range	110-300 VAC ± 5% at 50% load 160-300 VAC ± 5 % at 100% load				110-300 VAC @ 0~60% load; 140-300 VAC @ 60~80 % load; 176-300 VAC @ 80~100 % load	
Frequency range	40 Hz ~ 70 Hz				46 ~54 Hz or 56~64 Hz	
Power factor	≥ 0.99 (100% Load)					
OUTPUT						
Output voltage	200/208/220/230/240 VAC				208/220/230/240 VAC	
AC Voltage Regulation (Batt. Mode)	± 1%					
Transfer Time AC to DC	Zero				Zero	
Transfer Time Inverter to Bypass	4 ms (Typical)				Zero	
Waveform (Batt. Mode)	Pure Sine wave					
EFFICIENCY						
Line Mode	≥ 91% @ battery fully charged					
ECO Mode	≥ 96% @ battery fully charged					
Battery Mode	≥ 90%				91%	
BATTERY						
Stander Battery type	12V/7 Ah or 12V/ 9 Ah					
External Battery type	Depending on applications (65AH - 200AH)					
Numbers	3	3	4	6	20	20
Typical Recharge Time	9 hours recover to 90% capacity					
Charging Current	200/208/220/230/240 VAC Models: default 2A, max. 12A				default 1A, max. 4A adjustable	
Charging Voltage	41.1 VDC ±1%	41.1 VDC ±1%	54.8 VDC ±1%	82.1 VDC ±1%	273 VDC ±1%	
ALARM						
Battery Mode	Sounding every 5 seconds					
Low Battery	Sounding every 2 seconds					
Overload	Sounding every second					
Fault	Continuously sounding					
ENVIRONMENTAL						
Humidity	20-90% RH @ 0- 45°C (Non-condensing)					
Noise Level	Less than 50dBA@1 Meter					
PHYSICAL						
Dimension D*W*H (mm)	410 x 438 x 88	410 x 438 x 88	510 x 438 x 88	630 x 438 x 88	600x438x88	
Net Weight (kgs)	14.1	15.5	19.5	27.5	15	18